Release Notes – Zebra TC51, TC51-HC, and TC56 Android N – LifeGuard Update 20 for NGMS

Introduction

Description

Device Compatibility

Component Contents

Installation Requirements

Installation Instructions

Downloadable Software Included in this Release

Introduction

Work more efficiently and better serve your customers by giving your employees enterpriseclass handheld computers that survive life in the field or shop floor, communicate and access information in real time.

The TC51/TC51-HC/TC56 is the professional-grade Android device built from the ground up for the enterprise.

- Zebra's Mobility Extensions (Mx)
- Mobility DNA, a suite of mobility enabling applications, development tools and utilities
- Most advanced scan engine with longer range date capture capability
- Rugged and ready for every day enterprise use inside and outside the four walls

Description

This release contains the following software package which is compatible with the TC51, TC51-HC and TC56 Non-GMS products.

LifeGuard patches are cumulative and include all previous fixes that are part of earlier patch releases.

Note:

When upgrading from M to N LG CFE, device should be upgraded to N first and allow to Reboot the device so that the Nougat LG Patch can be installed.

Component Contents

Component / Description	Version	
Product Build Number	01-01-49.00-NN-U20-STD	
Android Version	7.1.2	
Linux Kernel	3.10.84	
Android SDK Level	25	
Platform	QC8956	
Bluetooth Stack	1.1	
Flash Size	32GB	
RAM Size	4GB	
Scanning	19.58.37.0	
DataWedge	7.3.26	
EMDK	7.3.21.2321	
MXMF / OSX	MXMF-9.0.4.3 / QCT.71.7.11	
Enterprise Keyboard (EKB)	2.1.1.3	
WiFi	FUSION_BA_2_10.0.4.026_N Application: BA_2_10.0.1.012_N Radio: BA_2_10.0.4.023_N Middleware: BA_2_10.0.1.014_N Firmware: 7.35.205.8 (r)	
PTT	3.1.35	
Touch FW	N/A	
RxLogger Utility	5.4.13.0	

B2M	N/A		
Bluetooth Pairing Utility	3.11		
Zebra Data Services	3.5.0.1145		
File Browser	1.19.1.5		
Stage Now	3.3.1.2000		
App Gallery	3.0.1.7		
User Guide	N/A		
Sensors (Accel, Gyro)	2061000, 2061000		
MobiControl	N/A		
Zebra Volume Control (ZVC)	2.0.0.16		
Battery Manager	1.3.8		
ActiveEdge	2.5.16		
WorryFreeWiFi (Smart MU)	3.0.3		
SimulScan Demo App	3.0.2		
SimulScan Engine	2.0.3		
Device Central	2.1.0.9		
Zebra Software License Manager	3.1.1		
Audio SW Version	0.24.0.0		
Acoustic Profiles	TC51HC: General: AN2.1 Cellular: N/A	TC56: General: AN3.6 Cellular: AN3.6	TC51: General: AN1.4 Cellular: N/A
Diagnostic Tool	1.17.0.9	1	•
Webview	73.0.3683.90		
FingerPrint	Zebra/TC56/TC56:7.1.2/01-01-49.00-NN-U20-STD/170:user/release-keys Zebra/TC51/TC51:7.1.2/01-01-49.00-NN-U20-STD/170:user/release-keys Zebra/TC51HC/TC51HC:7.1.2/01-01-49.00-NN-U20-STD/170:user/release-keys		

1. CFE v20 Updates:

CFE ATLAS 01-01-49.00-NN-U20-STD.zip (NGMS)

1. Android Security Patch Level: September 1, 2019

Use the link below to see the Android Security bulletin for more information: https://source.android.com/security/bulletin/

- 2. MX, StageNow, EMDK, Datawedge, Enterprise keyboard component updates:
 - o MX: v9.0.4.3
 - a. SPR36581 Resolved an issue wherein MX was returning invalid package name error when SOTI was being enrolled as DO.
 - o EMDK: v7.3.21.2321
 - o Datawedge: v7.3.26
- 3. OSX Version QCT.71.7.11
- 4. SPR37601 Resolved an issue wherein user was unable to set en_IE locale using UIMgr CSP.
- 5. SPR37150/37520 Resolved an issue wherein devices with SOTI were stuck at the boot animation screen.
- 6. SPR36163 Resolved an issue wherein DHCP Option exception causing device reboot.
- 7. SPR36961 Resolved an issue wherein Zebra RFID Mobile app (APK) disappears from app menu after reboot.
- 8. SPR38042 Resolved an issue wherein disabling Doze mode through Stage now was failing.
- 9. SPR37462 Resolved an issue wherein invalid battery swap would leave the device in Airplane mode.
- 10. SPR36967 Resolved an issue wherein downgrading from Latest patch (LG20) to older patch (LG19) causing ZDS crash.

Known issue:

"Zebra Data Service Plugin has stopped" Pop-up has been observed while downgrading from latest patch (LG20) to older patches (LG18 downwards).

2. CFE v19 Updates:

- ❖ CFE ATLAS 01-01-49.00-NN-U19-STD.zip (NGMS)
- 1. Android Security Patch Level: June 1, 2019

- 2. MX, StageNow, EMDK, Datawedge, Enterprise keyboard component updates:

 Note: For detailed release notes, please refer http://techdocs.zebra.com
 - o MX: v9.0.3.1
 - a. SPR36994 Resolved MX initialization issue wherein EHS was calling MX before completion of MX initialization process.
 - b. SPR36768 Resolved an issue wherein EHS Hostname in title was not reflecting updated HostName after device reboot.
 - c. SPR36581 Resolved an issue wherein MX was returning invalid package name error when SOTI was being enrolled as DO.
 - d. SPR36479 Resolved an issue where mapping a key using Key Manager CSP to trigger an intent was not working.
 - StageNow: v3.3.1.2000Datawedge: v7.3.22
 - a. SPR37124 Resolved an issue where in ADF rule with crunch spaces was removing last character from barcode data with space.
 - o EMDK: v7.3.18.2318
 - o DDT: v1.17.0.9
 - Enterprise Keyboard: v2.1.1.3
 Scanner Framework: v19.58.37.0
 - a. SPR37064 Resolved wrong property.
 - b. SPR36685 Resolved an issue wherein scan engine was failed to initialize during powerup.
 - c. SPR37175 Resolved an issue where in multiple application can enable the same scanner without one app releasing it.
 - d. SPR-37014 Disable firmware update on 8956 N Products.
 - e. SPR 37201 Resolved an issue wherein scan HardTrigger stops working once Language Settings are modified.
 - f. SPR36927 Resolved an issue where scanner was not available for any app when multiple apps enable the scanner and any app among disable the scanner when it moves to background.
 - g. SPR37060/SPR36880 Resolved an issue wherein Datawedge was not disabling the scanner upon resume during app transition from background to foreground causing intermittent scanning failures.
 - h. SPR36925 Resolved an issue wherein scanner was not available for second app when an ANR or crash occurred on the first app
 - i. Integrated new imgkit version IMGKIT_8.02T01.16.
 - o Wifi: FUSION BA 2 10.0.4.026 N
 - a. SPR36741 Resolved an issue wherein device is taken long time to connect in case of failure scenario.
 - b. SPR36855 Resolved an issue where WiFi becomes disabled after reboot because of a GPS module exception.

- RxLogger Version 5.4.13.0
- Diagdaemon Version 5.4.16.0
- WebViewGoogle Version 73.0.3683.90
 - a. SPR35943 Updated Chromium Webview for NGMS releases.
- OSX Version QCT.71.7.10
- Zebra Data Services Version 3.5.0.1145
- o Device Central: v2.1.0.9
 - a. Added support to start scan and pair by squeezing hardware scan trigger.
- 3. SPR36961 Resolved an issue wherein Zebra RFID Mobile app (APK) disappears from app menu after reboot.
- 4. SPR36958 Resolved an issue wherein disabling Airplane Mode using PowerKey Manager is not working
- 5. SPR37152 Resolved an issue wherein devices has trouble reading and connecting to devices over NFC.
- 6. SPR36691 Resolved an issue wherein location gets turned off on every reboot.
- 7. SPR36600/37084 Resolved an issue wherein device would not boot to the OS due to an exception while removing packages.
- 8. SPR36897 Updated Telstra M2M APN with DUN type.
- 9. SPR36658 Made a change to perform correction on unsealed batteries.
- 10. SPR36294 Resolved an issue with scanner wherein the imager was not configured correctly during boot up.
- 11. SPR36396 Resolved an issue wherein device not connecting to network with China Unicom SIM.
- 12. SPR36879 Adding scan code POUND and STAR.
- 13. SPR36347 Resolved an issue wherein SIP was showing irrespective of "Show Virtual Keyboard" on first launch of chrome browser.
- 14. SPR36691/37039 Resolved an issue wherein Airplane mode gets greyed out after reboot.
- 15. SPR37380 Resolved an issue wherein "Memory" in Settings app was translated wrongly in Deutsch(Deutschland).
- 16. SPR36778 Resolved an issue wherein Static IP address was not being set using Ethernet Manager.
- 17. SPR37404 Resolved an issue wherein Airplane mode gets greyed out after reboot.

Known issue:

"Zebra Data Service Plugin has stopped" Pop-up has been observed while downgrading from latest patch (LifeGuard 19) to other patches

3. CFE v18 Updates (Removed from support portal):

- CFE ATLAS 01-01-49.00-NN-U18-STD.zip (NGMS)
- 1. Android Security Patch Level: March 1, 2019

- 2. Updated below mentioned components:
 - OSX Version QCT.71.7.9.1
 - a. SPR35906 Resolved an issue in EHS system restricted settings.
 - Scanner Framework: Version 19.54.37.0
 - a. SPR36333 Resolved an issue wherein enabling DW simulscan option locks up device after suspend/resume.
- 3. SPR36262 Resoled an issue wherein NTP parameters were not updated when applied through Stagenow.
- 4. SPR36165 Added Supported LTE bands in the specific hardware.
- 5. Enabled Native Screen Blanking service.

4. CFE v17 Updates (Removed from support portal):

CFE ATLAS 01-01-49.00-NN-U17-STD.zip (NGMS)

CFE v16 numbering is skipped for public posting and reserved for LGE-FOTA Beta.

1. Android Security Patch Level: February 1, 2019

- 2. MX, StageNow, EMDK, Datawedge, Enterprise keyboard component updates:
 - **Note**: For detailed release notes, please refer http://techdocs.zebra.com
 - o MX: v8.4.1.3
 - a. SPR35491/35856 Resolved an issue where in Analytics Manager was throwing "Index out of bound error " when a Stagenow Barcode is scanned.
 - b. SPR35928 Resolved an issue where Clock Manager CSP accepts timezone id in "/Etc" Olson format.
 - c. SPR35908 Resolved an issue wherein admin and user generated certificates could not be downloaded from external server.
 - d. SPR35855 Resolved an issue where in Google Keyboard settings was not persisting.
 - Enterprise Keyboard: v2.0.1.9
 - StageNow: v3.2.1.0EMDK: v7.2.2.2202DataWedge: v7.2.5
 - o DDT: v1.16.1.3
 - Oem Config: v8.4.0.1
 - o WorryFreeWiFi (SMARTMU): v3.0.3
 - a. Added support for WorryFree WiFi CSP
 - o Device Central: v2.0.22.1
 - a. SPR36473 Show the Battery percentage on the Device Central App main screen when DS3678-ER connected to the mobile device.

- Wifi: FUSION BA 2 10.0.4.025 N
 - a. SPR36248 Resolved an issue where StageNow configuration will not work with TC75x HW ID 33 device.
 - b. SPR35982 Resolved an issue where roaming failure is observed in disconnect suppression state.
 - c. SPR36361 Enhanced device performance by increasing the value of wlan retries to 12 from the current value of 7.
 - d. SPR35825 Resolved an issue wherein one-way audio is observed during a call sometimes.
 - e. SPR36075 Fixed an issue wherein voice packets were not tagged with correct QoS category sometimes which might have caused choppiness in audio call.
- 3. SPR36275 Resolved an issue where-in Camera swap option was still visible in camera App even after disabling one of the camera [Front/Rear] in TC7x devices via StageNow.
- 4. SPR36344 Resolved an issue wherein device radio states are not recovered if incorrect Battery Swap is performed.
- 5. SPR36213 Resolved an issue wherein device would reboot upon enabling data saver when Bluetooth tethering is enabled in DO mode.
- 6. SPR35347 Resolved an issue wherein device would not boot to the OS after enabling data saver in DO mode.
- 7. SPR35950 Resolved an issue wherein SwiftKey Keyboard Breaks Scanning After Reboot.
- 8. SPR35991 Resolved an issue wherein when soft-keyboard is switched, sometimes Scan data stops to transmit to apps.
- 9. SPR35523 Resolved an issue where on disabling Airplane Menu in power key menu, this caused Cellular network settings to be greyed out in settings.

5. CFE v15 Updates (Removed from support portal):

- CFE_ATLAS_01-01-49.00-NN-U15-STD.zip (NGMS)
- 1. Android Security Patch Level: January 1, 2019

- 2. Updated below mentioned components:
 - WiFi: FUSION BA 2 10.0.3.020 N:
 - a. SPR35628 Resolved an issue where validation of Radius server certificate fails.
 - b. SPR35593 Resolved a device reboot issue where DHCP Option received with more than expected length.
 - Scanner Framework: Version 19.50.37.0

- a. SPR35288 Fixed an issue wherein initialization of scanner was taking ~1sec.
- b. SPR35054 Added support for reduced quite zone barcode decoding.
- c. SPR34844 Resolved an issue wherein multiple open calls are prevented when multiple application tries to open scanner without releasing previous instance.
- OSX Version QCT.71.7.9
 - a. SPR36117/36095 Resolved an issue wherein the scanned data would not come to the Apps, Airplane menu item was missing in the Power key menu and Home and recent buttons were not functional
- 3. SPR35414 Resolved an issue to differentiate BT scanners and to avoid multiple paring and un-paring events.
- 4. SPR36019 Resolved an issue wherein serial port control signals were not working as expected.

6. CFE v14 Updates:

- ❖ CFE ATLAS 01-01-49.00-NN-U14-STD.zip (NGMS)
- 1. Android Security Patch Level: December 1, 2018

Use the link below to see the Android Security bulletin for more information: https://source.android.com/security/bulletin/

- 2. SPR35256 Resolved an issue causing NTP synchronization failure.
- 3. SPR35065 Resolved an issue to include the correct EXIF orientation tag data, in the jpeg image capture by camera.
- 4. SPR34861 Resolved an issue wherein earlier versions of velocity app installation (1.x) was not persisting after reboot.
- 5. SPR35845 Resolved an issue wherein, Gallery Application in Non-GMS displays the pictures with incorrect orientation.

7. CFE v13 Updates:

- ❖ CFE ATLAS 01-01-49.00-NN-U13-STD.zip (NGMS)
- Android Security Patch Level: November 1, 2018
 Use the link below to see the Android Security bulletin for more information: https://source.android.com/security/bulletin/
- 2. MX, StageNow, EMDK, Datawedge, Enterprise keyboard component updates:

Note: For detailed release notes, please refer http://techdocs.zebra.com

- o MX: 8.2.3.1
 - b. SPR35665 Resolved an issue wherein Google keyboard settings are not persisting through a reboot when configured directly after factory reset.
 - c. SPR34771 Resolved a synchronization issue in Mx.
- StageNow client: 3.1.1.1019
- EMDK: 7.0.0.2000DataWedge: 7.0.4
- Enterprise Keyboard: 1.9.0.9
 - a. SPR35603 Fixed an issue wherein Enterprise Keyboard was disappearing when an external keyboard was connected.
- 3. SPR35692 Fixed an issue where it was not possible to disable "Show virtual keypad" from "Settings / Languages & Input / Physical Keyboard".
- 4. Added enable/disable Settings drawer feature implementation in OSX.
- 5. B2M client included in disabled mode.

8. CFE v12 Updates:

- CFE_ATLAS_01-01-49.00-NN-U12-STD.zip (NGMS)
- 1. Android Security Patch Level: October 1, 2018

- 2. Updated below mentioned components:
 - WiFi: FUSION BA 2 10.0.3.019:
 - a. Enable/Disable FAPI support to turn ON/OFF hotspot via CSP.
 - b. SPR34760 Resolved an issue wherein the device was unable to reconnect after some idle hours in low coverage.
 - c. Enable/Disable Captive Portal Support.
 - o SmartMU: Version 3.0.2:
 - a. SmartMU app name change to WorryFreeWiFi
 - Device Central: Version 2.0.17.0
 - Scanning Framework: Version 19.11.37.1
 - a. SPR34484 Resolved an issue wherein exceptions were not thrown when multiple apps try to open scanner instance without earlier instance being released.
- 3. SPR34300 Added Auto Screen Rotation to Lock screen.
- SPR35090 Resolved an issue wherein disabling captive portal detection was not working.

- 5. SPR35065 Resolved an issue to include the correct EXIF orientation tag data in the jpeg image capture by camera.
- 6. SPR35462 Fixed an issue wherein keyboard selection notification was being shown on hard keypad devices.
- 7. SPR35216 Resolved an issue where Proxy Auto Config (PAC) did not work properly following stops/restarts of the PacService
- 8. SPR35188 Disabled QC Quick Charge 3.0 which allows the device to charge at 9v (since many 3rd party cables are rated for only 5v use).
- 9. SPR34978 Resolved an issue wherein the device was unable to set private apn through EMDK or StageNow.
- 10. SPR35021 Resolved an issue where Auto PAC Proxy settings are not preserved after Android desert update.
- 11. Added new APN for Telstra-M2M.

9. CFE v11 Updates:

- CFE_ATLAS_01-01-49.00-NN-U11-STD.zip (NGMS)
- 1. Android Security Patch Level: September 1, 2018

Use the link below to see the Android Security bulletin for more information: https://source.android.com/security/bulletin/

- 2. Updated below mentioned components:
 - Enterprise Keyboard: Version 1.9.0.4
 - Diagnostic Tool: Version 1.16.0.1
 - OEMConfig: Version 8.1.0.9
 - Device Central: Version 2.0.11.0
 - Zebra Software License Manager: Version 3.1.1
 - Zebra Data Services: Version 1.0.0.1002
- 3. MX, StageNow, EMDK, Datawedge component updates:

Note: For detailed release notes, please refer http://techdocs.zebra.com

- MX: Version 8.1.0.10
- StageNow: Version 3.1.1.1018
- o EMDK: Version 6.10.12.1312
- Datawedge: Version 6.9.49
 - a. SPR34429 Resolved an issue wherein DataWedge failed to load "default Profile0".
 - SPR34614 Resolved an issue in DataWedge wherein scanner could not be enabled due to quick enabling and disabling of scanner through Intents.

- SPR34972 Implemented new parameters in scanner_input_plugin
 API so that the API takes considerable less time to suspend/reenable
 of the scanner
- 4. CVE-2018-5383 was corrected preventing unauthenticated BT pairing.
- 5. SPR34970 Resolved an issue wherein speech quality was not good for WAN calls on TC56.
- 6. Added LEAP Profile support.
- 7. Included Zebra Software License Manager v3.1.1.
- 8. Data Analytics changes:
 - DataAnalytics has been renamed to Zebra Data Service.
 - o DAInBuiltDCA has been renamed to Zebra Data Service Plugin.
 - SettingsEULA has been renamed to Zebra Data Services.
 - In this release, the ZDS-EULA pop up during configuring the device, can be automatically skipped if the device is configured for Device Owner mode or when SUWBypass is used.
 - DO mode configuration mechanism includes NFC bump, QR code, AFW# and Zero touch.
 - SUW Setup Wizard Bypass can set with PowerMgr CSP.
 - On Automatic skipping of Zebra EULA, Zebra's default settings and data collection rules will be configured on the device.
- 9. Device Central v2.0:
 - Device Central v2.0 support is claimed for TC56 N.
 - Ability to scan Bluetooth MAC address barcode and pair the supported peripherals such as HS3100 Headset, Zebra Printer.
 - Ability to scan-to-pair supported Bluetooth scanner such as RS6000, DS3678
 - Ability to display supported paired devices list in Device Central App Summary Page.
 - Ability to unpair the supported paired Peripherals such as HS3100 Headset,
 Zebra Printer.
 - Ability to keep only one paired device of same class and unpair previously paired device of same class for the supported peripherals such as Printer, HS3100 Headset.
 - Ability to configure the Device Central application UI using Device Central Manager CSP
 - a. Enable/disable firmware update option in device central (Default firmware update option is enabled).
 - b. Enable/disable user to turn on/off Bluetooth Power from Device Central App.

c. Ability to keep only one paired device of same class and unpair previously paired device of same class for the supported peripherals.

10. CFE v10 Updates:

CFE_ATLAS_P10_NN_01-01.49.zip (NGMS)

1. Android Security Patch Level: August 1, 2018

Use the link below to see the Android Security bulletin for more information: https://source.android.com/security/bulletin/

- 2. Updated below mentioned components:
 - OSX Version QCT.71.7.7.1
 - Scanning Framework Version 19.11.37.0
- 3. SPR34695 Resolved an issue wherein Google play protect setting was not persisting across reboot.
- 4. SPR35062 Resolved an issue wherein setting Default Launcher was failing when more than one third party launcher was installed in the device.
- 5. SPR34648 Resolved an issue where malformed DHCP Option 150 (TFTP Server Address) was passed during DHCP exchange.
- SPR34445 Resolved an issue wherein scanner exceptions were observed while scanning DATAMATRIX barcodes using DS3678 scanner resulting in scanner beam failures.
- 7. SPR34310 Resolved an issue where in CANCELREAD API was not working when Continuous Mode was enabled.
- 8. SPR34757 Resolved an issue where DHCP Option 42 (NTP servers) has more entries than expected.
- SPR34046 Resolved an issue wherein there were Bluetooth scanner disconnections noticed while audio was being played simultaneously on BT headset.

11. CFE v9 Updates:

❖ CFE ATLAS P09 NN 01-01.49.zip (NGMS)

1. Android Security Patch Level: July 1, 2018

- 2. Updated below mentioned components:
 - MX Version 8.0.2.0
 - o EKB Version 1.8.0.8
 - StageNow Client Version 3.0.1.1038

- DataWedge Version 6.8.54
- WiFi FUSION BA 2 10.0.1.019 N
- SmartMU Version 3.0.1
- OSX Version QCT.71.7.7.0
- DataAnalytics Version 3.3.0.1113
- 3. After an upgrade from non-EULA to EULA BSP, the Data Analytics Engine (DAE) upgrades to v3.3.0.1113 and takes about 35 secs to initialize for the first time. During this time the Settings->Zebra (EULA) page will show the default status of Device Data toggle button as enabled until initializing is complete.
- 4. Audio Optimization resulting in a 75% reduction is buffering between HAL and ALSA in both the RX and TX leg of a VoIP Call reducing device's contribution to the mouth to ear delay significantly. Impact is to VoIP use case only on all SKU's.
- 5. SPR34894 Fixed an issue in DataWedge wherein scanner could not be enabled due to quick enabling and disabling of scanner through Intents.
- 6. SPR34743 Keyboard configuration properties has been changed for software keyboard pop up scenario.
- 7. SPR34906 Resolved an issue wherein device used to get stuck in the boot up screen on Velocity app installed devices.
- 8. SPR33599 Resolved an issue wherein few system apps were being disabled after Applock whitelist mode was enabled.
- SPR33818 Fixed an issue wherein certain decoder type values were not persisting across a scanner enable/disable cycle.
- 10. SPR34267 Resolved an issue wherein user was not able to enable USB debugging option using StageNow.
- 11. SPR33639 Resolved an issue wherein the customer app install and launch during device sleep state and device stop emitting scan beam after awake from suspend.
- 12. SPR33920 Resolved an issue wherein devices failed to connect to WLAN network if the country selection is set to Japan.
- 13. SPR34717 Added support for new method of creating the Applock Whitelist.
- 14. SPR34888 Resolved an issue wherein user could not launch Key Programmer in Settings App.
- 15. SPR34595 Resolved an issue wherein Storage Card path was inaccessible through StageNow.
- 16. SPR34346 Resolved an issue wherein Velocity app installation was not persisting after reboot.

12. CFE v8 Updates:

❖ CFE ATLAS P08 NN 01-01.49.zip (NGMS)

1. Android Security Patch Level: June 1, 2018

Use the link below to see the Android Security bulletin for more information: https://source.android.com/security/bulletin/

- 2. Resolved an issue wherein KeyProgrammer fails to open via Device settings.
- 3. Build Number format has been updated.

13. CFE v7 Updates:

- ❖ CFE ATLAS P07 NN 01-01.49.zip (NGMS)
- 1. Android Security Patch Level: May 1, 2018

Use the link below to see the Android Security bulletin for more information: https://source.android.com/security/bulletin/

- 2. Fix for Zebra setup wizard popup after OS upgrade.
- 3. Updated below components:

o MX: 8.0.0.10

StageNow client: 3.1.0.1037

o DataWedge: 6.8.50

Enterprise Keyboard: 1.8.0.8

- 4. Build ID format has been updated.
- 5. Included Zebra Software License Manager v3.0.1.
- 6. SPR34179 Resolved an issue wherein device connects slowly to an AP.
- 7. SPR34175 Resolved an issue wherein device does not show preview information in Messaging App when language toggles from right-to-left.
- 8. SPR34259 Added support to use USBMgr CSP to limit the standard 4 options on device to only allow UsbExternalStorageUsage.
- 9. SPR34307 Resolved an issue wherein the device was unable to be staged via StageNow.
- 10. SPR34083/34014/32519 Resolved an issue wherein disabling WWAN radio via Airwatch using StageNow XML fails.
- SPR33977 Resolved an issue wherein set time zone issue observed with StageNow.
- 12. SPR34213/31491 Resolved an issue wherein the device was unable to stage via StageNow.
- 13. SPR34420 Resolved an issue wherein floating scan bubble issue observed with Enterprise Keyboard.
- 14. SPR33755 Resolved an issue wherein the Whitelisted apps were unable to submit XML to MX.

- 15. SPR33207 Resolved an issue wherein the Device Diagnostic tool had an issue with reading the Battery Cycles in the application for PP+ batteries.
- 16. SPR33671 Resolved an issue wherein user was unable to create WIFI profile with username as backslash followed by number.
- 17. SPR33862 Resolved an issue wherein the Screen Time off settings using Display manager CSP was not working.
- 18. SPR34145 Resolved an issue wherein indexing of the WEP key was not handled correctly.
- 19. SPR33973 Resolved an issue wherein erroneously loading default profile by providing feature to ignore disabled profiles in DataWedge.
- 20. SPR33848 Added support to included category field in intent profile in StageNow.
- 21. SPR34189 Resolved an issue wherein low ram and oom limit adjustments to provide more free memory.
- 22. SPR33876 Resolved an issue wherein Display Timeout was unable set via StageNow.
- 23. SPR33607 Resolved an issue where few fresh devices were unable to stage after unbox the device.
- 24. SPR33538 Resolved an issue wherein the Scanner beam stuck off and No LED beam while pressing scanner button.
- 25. SPR33981 Resolved an issue Czech Republic Regulatory Country could not be set using Wifi config profile.
- 26. Added Enterprise Browser package (com.symbol.enterprisebrowser) to white listed apps.
- 27. Resolved an issue wherein Settings App crashes while performing "Network Settings Reset".
- 28. Resolved an issue wherein Bluetooth tethering was not working.
- 29. Added support for RS507x.
- 30. Fixed Bluetooth scanner firmware update failure.
- 31. Fixed "SignalOccurrenceOfThreat" parm is not added in threatStep.
- 32. SPR34579 Resolved an issue wherein headset audio volume is too low when used with VoIP applications.
- 33. New Audio tuning for TC51/56 devices. This is a general enhancement to the original tuning to increase VoIP headset volume and to satisfy new regulatory requirements. The changes improve audio performance for telephone use cases such as VoIP, PTT, WAN, and VoLTE. Note that these changes are not applicable to TC51 HC SKUs.

34. A new device settings menu and an initial setup screen have been added to easily configure the Zebra analytics engine. The initial setup screen will be displayed upon bootup following an Enterprise Reset or Factory Reset. This screen can be skipped on an Enterprise Reset by provisioning using a StageNow profile (PowerMgr CSP), similar to what is available for the Google setup wizard bypass.

14. CFE v4 Updates:

CFE-TC5X TC7Xx-01-01-49-NN-00-A-04.zip (NGMS)

1. Android Security Patch Level: March 5, 2018

Use the link below to see the Android Security bulletin for more information: https://source.android.com/security/bulletin/

2. Updated below components:

Datawedge: 6.7.34StageNow: 2.10.1.1386EMDK: 6.8.20.1120

o MX: 7.2.0.6

o File browser: 1.19.1.2

- 3. Added support for FIPS.
- 4. SPR33311 Resolved an issue wherein RS507 is unable to connect via Bluetooth using Voxware voice application.
- 5. SPR33302 Resolved an issue wherein disabling the oval capacitive key via StageNow fails.
- 6. SPR34267 Resolved an issue wherein USB debugging failed to get enabled via StageNow.
- 7. SPR33639 Resolved an issue wherein device stops emitting scan beam after waking up from suspend state.
- 8. SPR33799 Resolved an issue wherein DataWedge was sending char 10 instead of char 13.

15. CFE v3 Updates:

- CFE-TC5X TC7Xx-01-01-49-NN-00-A-03.zip (NGMS)
- 1. Spectre and Meltdown (CVE-2017-5753, 5715, 5754) remediation provided by updates to timer access for CVE-2017-13218.

Device Compatibility

This software release has been approved for use with the following Zebra devices. All devices listed below are on Android M or N when they leave the factory.

Device	Operating System
TC510K-2PAZU2P-US	Android N
TC510K-2PAZU2P-A6	Android N
TC510K-2PAZU4P-US	Android N
TC510K-2PAZU4P-A6	Android N
TC510K-2HDZU2P-US	Android N
TC510K-2HDZU4P-US	Android N
TC510K-2HDZU2P-A6	Android N
TC56DJ-2PAZU2P-A6	Android N
TC56DJ-2PAZU4P-A6	Android N
TC56DJ-2PAZU2P-IA	Android N
TC56DJ-2PAZU4P-IA	Android N
TC56DJ-2PAZU4P-BR	Android N
TC56DJ-2PAZU2P-BR	Android N
TC56DJ-2PAZU2P-CN	Android N
TC56DJ-2PAZU4P-CN	Android N
TC56DJ-2PAZU4P-ID	Android N
TC56DJ-2PAZU2P-ID	Android N
TC56DJ-2PAZU2P-TN	Android N
TC56DJ-2PAZU4P-TN	Android N

Supported FIPS SKUs

Device	Operating System
TC510K-2PAZU4P-FT	Android N
TC510K-2HDZU4P-FT	Android N
TC56CJ-2PAZU4P-FT	Android N

Installation Requirements

Install baseline 01-01-49-NN-00-A (NGMS) build.

Installation Instructions

Using ADB Sideload

The installation instructions assume you have ADB installed on your PC (the adb drivers and such) and your TC51/TC51-HC/TC56 has Developer options enabled and USB debugging ON:

Instructions on HOW TO enable ADB is also captured in Integrator guide.

- 1. Plug the TC51/TC51-HC/TC56 into the USB & Charging Cable and then the Cable to the PC. If you have a Cradle with USB connectivity, connect it now.
- 2. You may need to pull down the top menu and if you see "USB for charging", touch it and then change it to "File transfers".
- 3. Open Command Prompt, run "adb devices" and check if you can see the device's serial number... If yes, proceed... if not, you will need to get the PC set up with the proper drivers or install an External SD Card.
- 4. You may also get a pop up on your PC (Win 7) that you will be connected as a Portable MediaPlayer... this can be ignored.

❖ Download Image

- a. **CFE ATLAS 01-01-49.00-NN-U20-STD.zip** listed above in content section
- b. Reset files (Optional)
- 5. Entering Recovery Mode
 - a. Choice 1: In Command Prompt, type "adb reboot recovery" and click enter.
 - b. Choice 2:
 - Reset and hold PTT key
 - When Zebra Technologies logo appears on the screen Release the PTT Key
- 6. Your TC51/TC51-HC/TC56 will reboot and put you on the Android Recovery screen.
- 7. if applying update via sideload Method
 - a. Use the Volume + and to highlight, "Apply update from ADB" and press the Power Key to select it
- 8. With your Command Prompt open in the Host machine, type "adb sideload" command and add a space and then drag and drop the CFE on to it and click enter.
 - a. Your PC screen will show files being installed and a little blue horizontal progress bar on your device will show status... and after about 6[∼] minutes (could be 10+ minutes if installing GMS) it should be done and you should be back at the Android Recovery screen.
 - b. Repeat above steps for all mandatory packages
- 9. "Reboot system now" is highlighted. Press the Power Key to Reboot.

- 10. Device reboots and you see Zebra on top and POWERED BY android at the bottom and after about 1 minute will transition to the TC51/TC51-HC/TC56 Touch Computer splash screen with 5 dancing white dots at bottom... it will stay at this screen for a little over another minute (could be another 7+ minutes if installing GMS) and then you are at the Factory "Welcome" screen.
- 11. If you installed a GMS BSP, you will need to complete the process by setting up Wi-Fi and E-mail accounts and such. If on AOSP (non-GMS), there is no process to follow.
- 12. At the Home Screen, we need to verify that the BSP upgrade took place and set the Date & Time.
 - a. Go to "Settings" and scroll down to "About phone" and look at the "Build number". It should start with "01-01-49.00-NN-U20-STD". Now you are on the correct BSP.
 - b. Setting the Date and Time. If you associate to a WLAN AP, do so now, as it should automatically set the time and date... the only thing left is to set the time zone. Go to "Settings" and scroll to and select "Date & time". Scroll down to and select "Select time zone", and scroll down to and select the appropriate time zone and you are done.
- 13. To Check the Android Patch Level after installing the CFE package in the device,
 - a. Settings->About Phone->SW Components: Device Update Version: 20
 - ADB Shell method: Execute following command from PC's command prompt:
 \$ adb shell getprop ro.device.patch.version
 \$ 20
- 14. Now you are all set to use your TC51/TC51-HC/TC56

Using External SD card

- 1. Plug the TC51/TC51-HC/TC56 into the USB & Charging Cable and then the Cable to the PC. If you have a Cradle with USB connectivity, connect it now.
- 2. You may need to pull down the top menu and if you see "USB for charging", touch it and then change it to "File transfers".
- Download "CFE_ATLAS_01-01-49.00-NN-U20-STD.zip" file and Reset Files (Optional) and drag & drop the files on External SD card
- 4. Entering Recovery Mode
 - a. Reset and hold PTT key
 - b. When Zebra Technologies logo appears on the screen Release the PTT Key
- 5. Your TC51/TC51-HC/TC56 will reboot and put you on the Android Recovery screen.

- 6. Applying update via External SD card
 - a. Use the Volume + and to highlight select option to "Apply update from SD card" and press the Power Key to select it.
 - b. Use the Volume + and to highlight package to be installed (CFE_ATLAS_01-01-49.00-NN-U20-STD.zip) and press the Power Key to select it.
 - c. Repeat above steps for all mandatory packages
- 7. "Reboot system now" is highlighted. Press the Power Key to Reboot.
- 8. Device reboots and you see Zebra on top and POWERED BY android at the bottom and after about 1 minute will transition to the TC51/TC51-HC/TC56 Touch Computer splash screen with 5 dancing white dots at bottom... it will stay at this screen for a little over another minute (could be another 7+ minutes if installing GMS) and then you are at the Factory "Welcome" screen.
- 9. If you installed a GMS BSP, you will need to complete the process by setting up Wi-Fi and E-mail accounts and such. If on AOSP (non-GMS), there is no process to follow.
- 10. At the Home Screen, we need to verify that the BSP upgrade took place and set the Date & Time.
 - a. Go to "Settings" and scroll down to "About phone" and look at the "Build number". It should start with "01-01-49.00-NN-U20-STD". Now you are on the correct BSP.
 - b. Setting the Date and Time. If you associate to a WLAN AP, do so now, as it should automatically set the time and date... the only thing left is to set the time zone. Go to "Settings" and scroll to and select "Date & time". Scroll down to and select "Select time zone", and scroll down to and select the appropriate time zone and you are done.
- 11. To Check the Android Patch Level after installing the CFE package in the device,
 - a. Settings->About Phone->SW Components: Device Update Version: 20
 - ADB Shell method: Execute following command from PC's command prompt:
 \$ adb shell getprop ro.device.patch.version
 \$ 20
- 12. Now you are all set to use your TC51/TC51-HC/TC56.

Downloadable Software Included in this Release

Package Name	Description
CFE_ATLAS_01-01-49.00-NN-U20-STD.zip	OTA incremental LifeGuard CFE v20 update software for Non-GMS build compatible for TC51, TC51-HC and TC56 products.

Last Revised: September 20, 2019